

TwistPort™ Shielded Adaptor V2 for RouterBoard

ADAPTOR FOR RB 9XX, 7XX, 4XX SERIES BOARDS

TwistPort™ Shielded Adaptor V2 introduces
wide frequency range of operation: 5180 - 6400 MHz!

The TwistPort™ Shielded Adaptor V2 for RouterBoard makes the RouterBoard™ 9 series, 7 series and 4 series compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick locking waveguide port. Installing compatible RouterBoards into the TwistPort™ Adaptor V2 is very simple and requires no tools.



TECHNICAL DATA

| | |
|--------------------|--|
| Antenna Connection | TwistPort™ - Quick Locking Waveguide Port |
| Radio Connection | 2x Right Angle MMCX |
| Materials | Insert - Aluminium Alloy Shield - Aluminium Body - UV stabilized and weather resistant ABS plastic |
| Flame Rating | UL 94 HB |
| Temperature | -40°C to +60°C (-40°F to +140°F) |
| Wind Survival | 160 km/h |
| Weight | 0.6 Kg / 1.3 lbs – single unit 0.7 Kg / 1.5 lbs – single unit incl. package 16.3 Kg / 36 lbs – carton (20 units) |
| Single Unit | Retail Box: 21.3 × 15.3 × 9 cm |
| 20 Units | Carton Box: 49 × 33 × 46 cm |

PERFORMANCE

| | |
|-----------------|-------------------|
| Frequency Range | 5180 - 6400 MHz |
| Polarization | Dual Linear H + V |
| VSWR Max | 1.8 |
| Impedance | 50 Ohm |

COMPATIBLE WIRELESS PLATFORMS

| | |
|--------------|---|
| RF elements® | any TwistPort™ Antenna |
| MikroTik™ | RouterBoard™ RB91x, RB92x, RB71x, RB411L, RB411GL |

PACKAGE CONTENTS

TwistPort™ Adaptor RB Body
TwistPort™ Adaptor RB Sticker A
TwistPort™ Adaptor RB Sticker B
Screw 2.9 x 6.5 mm (4 pcs)

PRODUCT DIMENSIONS

